

ESD Protection Diode


Description

The GSDXXC is designed to replace multilayer varistors (MLVs) in portable applications such as cell phones, notebook computers and PDA's, using monolithic silicon technology to provide fast response time and ultra low ESD clamping voltage, making this device an ideal solution for protecting sensitive semiconductor components from damage. The GSDXXC complies with the IEC 61000-4-2 (ESD) with $\pm 30\text{kV}$ air and $\pm 30\text{kV}$ contact discharge. The ASDXXC is assembled into a lead-free SOD-323 package and will protect one unidirectional line. These devices will fit on the same PCB pad area as an 0805 MLV device.

Features

- 500W peak pulse power (8/20 μs)
- Protects one data or power line
- Ultra low leakage: nA level
- Operating voltage: 3.3V, 5V, 8V, 12V, 15V, 24V, 36V, 40V
- Ultra low clamping voltage
- Complies with following standards:
 - IEC 61000-4-2 (ESD) immunity test
 - Air discharge: $\pm 30\text{kV}$
 - Contact discharge: $\pm 30\text{kV}$
- RoHS Compliant
- AEC-Q101 qualified (Automotive grade with suffix "Q".)
- Expsemi electronics

Dimensions and Pin Configuration



SOD-323

Mechanical Characteristics

- Package: SOD-323
- Lead Finish: Matte Tin
- Case Material: "Green" Molding Compound.
- Moisture Sensitivity: Level 3 per J-STD-020
- Terminal Connections: See Diagram Below
- Marking Information: See Below

Applications

- Cellular Handsets and Accessories
- Personal Digital Assistants
- Notebooks and Handhelds
- Portable Instrumentation
- Peripherals
- Pagers Peripherals
- Desktop and Servers

Marking Information



Part Number	Marking
GSD33C	33
GSD05C	05
GSD08C	08
GSD12C	12
GSD15C	15
GSD18C	18
GSD24C	24
GSD36C	36
GSD40C	40

Ordering Information

Part Number	Packaging	Reel Size
GSDXXC	3000/Tape & Reel	7 inch

Absolute Maximum Ratings ($T_A=25^\circ\text{C}$ unless otherwise specified)

Parameter	Symbol	Value	Unit
Peak Pulse Power (8/20μs)	Ppk	500	W
ESD per IEC 61000-4-2 (Air) ESD per IEC 61000-4-2 (Contact)	VESD	±30 ±30	kV
Operating Temperature Range	TJ	-55 to +125	°C
Storage Temperature Range	Tstg	-55 to +150	°C

Electrical Characteristics ($T_A=25^\circ\text{C}$ unless otherwise specified)

GSD33C						
Parameter	Symbol	Min	Typ	Max	Unit	Test Condition
Reverse Working Voltage	VRWM			3.3	V	
Breakdown Voltage	VBR	3.8			V	IT = 1mA
Reverse Leakage Current	I _R			0.2	µA	VRWM = 3.3V
Clamping Voltage	V _C			5	V	IPP = 1A (8 x 20µs pulse)
Clamping Voltage	V _C			12.5	V	IPP = 40A (8 x 20µs pulse)
Peak Pulse Current	I _{PP}			40	A	tp = 8/20µs
Junction Capacitance	C _J		120	200	pF	VR = 0V, f = 1MHz

GSD05C						
Parameter	Symbol	Min	Typ	Max	Unit	Test Condition
Reverse Working Voltage	VRWM			5	V	
Breakdown Voltage	VBR	6			V	IT = 1mA
Reverse Leakage Current	I _R			0.2	µA	VRWM = 5V
Clamping Voltage	V _C			9.5	V	IPP = 1A (8 x 20µs pulse)
Clamping Voltage	V _C			15	V	IPP = 34A (8 x 20µs pulse)
Peak Pulse Current	I _{PP}			34	A	tp = 8/20µs
Junction Capacitance	C _J			200	pF	VR = 0V, f = 1MHz

GSD08C						
Parameter	Symbol	Min	Typ	Max	Unit	Test Condition
Reverse Working Voltage	VRWM			8	V	
Breakdown Voltage	VBR	8.5			V	IT = 1mA
Reverse Leakage Current	IR			0.2	µA	VRWM = 8V
Clamping Voltage	VC			10	V	IPP = 1A (8 x 20µs pulse)
Clamping Voltage	VC			14	V	IPP = 36A (8 x 20µs pulse)
Peak Pulse Current	Ipp			36	A	tp = 8/20µs
Junction Capacitance	CJ		100		pF	VR = 0V, f = 1MHz

GSD12C						
Parameter	Symbol	Min	Typ	Max	Unit	Test Condition
Reverse Working Voltage	VRWM			12	V	
Breakdown Voltage	VBR	13.3			V	IT = 1mA
Reverse Leakage Current	IR			0.2	µA	VRWM = 12V
Clamping Voltage	VC			19	V	IPP = 1A (8 x 20µs pulse)
Clamping Voltage	VC			28	V	IPP = 18A (8 x 20µs pulse)
Peak Pulse Current	Ipp			18	A	tp = 8/20µs
Junction Capacitance	CJ		60	100	pF	VR = 0V, f = 1MHz

GSD15C						
Parameter	Symbol	Min	Typ	Max	Unit	Test Condition
Reverse Working Voltage	VRWM			15	V	
Breakdown Voltage	VBR	16.7			V	IT = 1mA
Reverse Leakage Current	IR			0.2	µA	VRWM = 15V
Clamping Voltage	Vc			20	V	IPP = 1A (8 x 20µs pulse)
Clamping Voltage	Vc			25	V	IPP = 16A (8 x 20µs pulse)
Peak Pulse Current	Ipp			16	A	tp = 8/20µs
Junction Capacitance	CJ		30	80	pF	VR = 0V, f = 1MHz

GSD18C						
Parameter	Symbol	Min	Typ	Max	Unit	Test Condition
Reverse Working Voltage	VRWM			18	V	
Breakdown Voltage	VBR	19.8			V	IT = 1mA
Reverse Leakage Current	IR			0.2	µA	VRWM = 18V
Clamping Voltage	Vc			25	V	IPP = 1A (8 x 20µs pulse)
Clamping Voltage	Vc			38	V	IPP = 13A (8 x 20µs pulse)
Peak Pulse Current	Ipp			13	A	tp = 8/20µs
Junction Capacitance	CJ			60	pF	VR = 0V, f = 1MHz




GSD24C						
Parameter	Symbol	Min	Typ	Max	Unit	Test Condition
Reverse Working Voltage	VRWM			24	V	
Breakdown Voltage	VBR	27			V	IT = 1mA
Reverse Leakage Current	IR			0.2	µA	VRWM = 24V
Clamping Voltage	Vc			40	V	IPP = 1A (8 x 20µs pulse)
Clamping Voltage	Vc			50	V	IPP = 10A (8 x 20µs pulse)
Peak Pulse Current	Ipp			8	A	tp = 8/20µs
Junction Capacitance	CJ		30	50	pF	VR = 0V, f = 1MHz

GSD36C


Parameter	Symbol	Min	Typ	Max	Unit	Test Condition
Reverse Working Voltage	VRWM			36	V	
Breakdown Voltage	VBR	38			V	IT = 1mA
Reverse Leakage Current	I _R			0.2	μA	VRWM = 36V
Clamping Voltage	V _C			48	V	IPP = 1A (8 x 20μs pulse)
Peak Pulse Current	I _{PP}			6	A	tp = 8/20μs
Junction Capacitance	C _J		20	30	pF	VR = 0V, f = 1MHz

GSD40C

Parameter	Symbol	Min	Typ	Max	Unit	Test Condition
Reverse Working Voltage	VRWM			40	V	
Breakdown Voltage	VBR	44			V	IT = 1mA
Reverse Leakage Current	I _R			0.2	μA	VRWM = 40V
Clamping Voltage	V _C			50	V	IPP = 1A (8 x 20μs pulse)
Peak Pulse Current	I _{PP}			5	A	tp = 8/20μs
Junction Capacitance	C _J		20		pF	VR = 0V, f = 1MHz


Typical Performance Characteristics ($T_A=25^\circ\text{C}$ unless otherwise Specified)

Peak Pulse Power vs. Pulse Time

Power Derating Curve

8 X 20μs Pulse Waveform

SOD-323 Package Outline Drawing



SYM	DIMENSION			
	MILLIMETERS		INCHES	
	MIN	MAX	MIN	MAX
A	1.50	1.80	0.060	0.071
B	1.20	1.40	0.045	0.054
C	2.30	2.70	0.090	0.107
D	-	1.15	-	0.043
E	0.30	0.40	0.012	0.016
F	0.10	0.25	0.004	0.010
H	-	0.10	-	0.004

Suggested Land Pattern



SYM	DIMENSIONS	
	MILLIMETERS	
	INCHES	INCHES
A	3.15	0.120
B	0.80	0.031
C	0.80	0.031